


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
A		CH'D -4 & -7 PRECISION FOR DIMENSION FROM .21 TO .205 PER G.E.	3/1/2012	RJC	GE
B	14-0142	-2 ADDED DIMENSION .503-.505. CH'D DIMENSION TOLERANCE ON NON-CRITICAL DIMENSION. -4, -5, -6, -7 CH'D DIMENSION TOLERANCE ON NON-CRITICAL DIMENSIONS. -7 ADDED ENGRAVE NOTE.	8/29/2014	DJN	GE
2	17-0157	UPDATED TO NEW DRAFTING STANDARD. -2, -4, -5, -6, -7 CH'D MAT'L WAS 4140 IS 4140/4142. -2, -3, -4, -5, -6, -7 ADDED FINISH SPEC QMSI-6.2.2. B.O REV D. -2 CH'D DIM WAS 1/4-28 UNF $\sqrt{110^\circ}$ X \varnothing .25 $\sqrt{.003}$ A IS 1/4-28 UNF -28 $\sqrt{.42}$ $\sqrt{\varnothing .25}$ X 110° NEAR SIDE $\sqrt{.003}$ A ADDED DIM 2X .670 MIN. -3 CH'D DIM WAS .060 IS .06. WAS .02 X 45° 1/4-28 UNF $\sqrt{.001}$ A IS 1/4-28 UNF -2A $\sqrt{.001}$ A. CH'D MAT'L WAS 4140 Q&T IS 4140/4142. ADDED FINISH IS QMSI-6.2.2. B.O. REV D. -4, -5, -6 CH'D DIM WAS 3.343 IS 3.34. ADDED ENGRAVE DASH # COLUMN TO TABLE. CH'D NOTE WAS ENGRAVE -# ONLY IS ENGRAVE SEE TABLE. -7 CH'D NOTE WAS ENGRAVE -# ONLY IS ENGRAVE "7".	6/20/2017	RJC	JAG



NOTES:
1. SEE SHEET 4 TABLE FOR DIMENSIONS
& TOLERANCES FOR -4 THRU -6.
2. ONE EACH -4 THRU -7 PER TOOL.



TITLE
ADJUSTABLE SPANNER WRENCH



DWG NO. RB AN8515-1

REV	2
-----	---

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.	MAT'L		UNLESS OTHERWISE SPECIFIED	
									HEAT TREAT FINISH		DIMENSIONS ARE IN INCHES	FRACTIONS ± 1/8
			-2	1	HANDLE	4140/4142		2	SPEC		.XXX ± .005	ANGLES ± 5°
			-3	1	BOLT	4140/4142		3	DRAWN BY: CLOUGH		.XX ± .01	SURFACES = 125/
			-4	1	ARM	4140/4142		4	CHECKED: DD 06/22/2017		.X ± .1	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
			-5	1	ARM	4140/4142		4	OPPS APPR: AA 06/26/2017			2. DIMENSIONAL LIMITS APPLY AFTER PLATING
			-6	1	ARM	4140/4142		4	QA APPR: JL 06/28/2017			3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
			-7	1	ARM	4140/4142		5	APPROVED: JAG 07/06/2017		USED ON MODEL BELL	
									SCALE 1:2	DATE 1/12/2012	SHEET 1 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS						
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED	
B	14-0142	-2 ADDED DIMENSION .503-.505. CH'D DIMENSION TOLERANCE ON NON-CRITICAL DIMENSION.	8/29/2014	DJN	GE	
2	17-0157	-2 CH'D DIM WAS 1/4-28 UNF $\sqrt{110^\circ \times \varnothing .25}$ $\sqrt{.003}$ A IS 1/4-28 UNF -28 $\sqrt{.42}$ $\sqrt{\varnothing .25 \times 110^\circ}$ NEAR SIDE $\sqrt{.003}$ A ADDED DIM 2X .670 MIN. CH'D MAT'L WAS 4140 IS 4140/4142. ADDED FINISH SPEC QMSI-6.2.2, B.O REV D.	6/20/2017	RJC	JAG	



②
HANDLE



TITLE
ADJUSTABLE SPANNER WRENCH

DWG NO. RB AN8515-1-2

REV	2
-----	---

MAT'L 4140/4142

HEAT RC 22-32
TREAT

FINISH BLACK ANODIZE

SPEC QMSI-6.2.2, B.O. REV D

DRAWN BY:	CLOUGH
-----------	--------

CHECKED:	DD 06/22/2017
----------	---------------

OPPS APPR:	AA 06/26/201
------------	--------------

QA APPR:	JL 06/28/2017
----------	---------------

APPROVED:	JAG 07/06/2017
-----------	----------------

SCALE	1:1	DATE
-------	-----	------

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN INCHES
XXX + .005 FRACTIONS $\pm 1/8$

.XX	± .01	ANGLES ±.5°
X	± .1	SURFACES 125/

1. BREAK ALL SHARP EDGES

1. BREAK ALL SHARP EDGES
.015 x 45° OR .015R

2. DIMENSIONAL LIMITS APPLY AFTER PLATING

3. INTERPRET DIM AND TOL PER
ASME Y14.5M-2009

ASME Y14.5M 2000	USED ON MODEL
------------------	---------------

	BELL
--	------


12/2012 SHEET 2 OF 5


SCALE	1:1
-------	-----

DATE	1/12/2012
------	-----------

SHEET 2 OF 5


REVISIONS						
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED	
2	17-0157	-3 CH'D DIM WAS .060 IS .06, WAS .02 X 45° 1/4-28 UNF <input checked="" type="checkbox"/> 1.001 <input type="checkbox"/> A IS 1/4-28 UNF -2A <input checked="" type="checkbox"/> 0.001 <input type="checkbox"/> A. CH'D MAT'L WAS 4140 Q&T IS 4140/4142. ADDED FINISH IA QMSI-6.2.2. B.O. REV D.	6/20/2017	RJC	JAG	



		
TITLE ADJUSTABLE SPANNER WRENCH		
DWG NO. RB AN8515-1-3		REV 2
MAT'L 4140/4142 HEAT TREAT RC 22-32 FINISH BLACK OXIDE SPEC QMSI-6.2.2, B.O. REV D		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125/√
DRAWN BY: CLOUGH CHECKED: DD 06/22/2017 OPPS APPR: AA 06/26/2017 QA APPR: JL 06/28/2017		1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
APPROVED: JAG 07/06/2017		USED ON MODEL BELL
SCALE 4:1	DATE 1/12/2012	SHEET 3 OF 5

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
A		CH'D -4 PRECISION FOR DIMENSION FROM .21 TO .205 PER G.E.	3/1/2012	RJC	GE
B	14-0142	-4, -5, -6 CH'D DIMENSION TOLERANCE ON NON-CRITICAL DIMENSIONS.	8/29/2014	DJN	GE
2	17-0157	-4, -5, -6 CH'D DIM WAS 3.343 IS 3.34. CH'D MAT'L WAS 4140 IS 4140/4142. ADDED FINISH BLACK OXIDE, SPEC QMSI-6.2.2. B.O. REV D. ADDED ENGRAVE DASH # COLUMN TO TABLE. CH'D NOTE WAS ENGRAVE -# ONLY IS ENGRAVE SEE TABLE.	6/20/2017	RJC	JAG



(-4) (-5) (-6)

ARM

AN PART NO.	ITEM	DIMENSION		ENGRAVE DASH # ONLY
		A ±.005	B ±.003	
AN8515-4	.16 PIN ARM	.160	.152	-4
AN8515-5	.25 PIN ARM	.190	.246	-5
AN8515-6	.31 PIN ARM	.250	.308	-6



NOTE:

1. SEE TABLE FOR PIN DIMENSION & TOLERANCE.

DART AEROSPACE	
TITLE ADJUSTABLE SPANNER WRENCH	
DWG NO. RB AN8515-1-4	REV 2
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED
HEAT TREAT RC 22-32	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2, B.O. REV D	.XX ± .01 ANGLES ± 5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125✓
CHECKED: DD 06/22/2017	1. BREAK ALL SHARP EDGES
OPPS APPR: AA 06/26/2017	.015 x 45° OR .015R
QA APPR: JL 06/28/2017	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
APPROVED: JAG 07/06/2017	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
SCALE 1:1	DATE 1/12/2012
USED ON MODEL BELL	
SHEET 4 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
A		CH'D -7 PRECISION FOR DIMENSION FROM .21 TO .205 PER G.E.	3/1/2012	RJC	GE
B	14-0142	-7 CH'D DIMENSION TOLERANCE ON NON-CRITICAL DIMENSIONS. ADDED ENGRAVE NOTE.	8/29/2014	DJN	GE
2	17-0157	-7 CH'D NOTE WAS ENGRAVE -# ONLY IS ENGRAVE "7". CH'D MAT'L WAS 4140 IS 4140/4142. ADDED FINISH SPEC QSMI-6.2.2, B.O. REV D.	6/20/2017	RJC	JAG



(7)
ARM

DART AEROSPACE	
TITLE ADJUSTABLE SPANNER WRENCH	
DWG NO. RB AN8515-1-7	REV 2
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED
HEAT TREAT RC 22-32	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2, B.O. REV D	.XX ± .01 ANGLES ± 5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125° ✓
CHECKED: DD 06/22/2017	1. BREAK ALL SHARP EDGES
OPPS APPR: AA 06/26/2017	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
QA APPR: JL 06/28/2017	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
APPROVED: JAG 07/06/2017	USED ON MODEL
SCALE 1:1	BELL
DATE 1/12/2012	SHEET 5 OF 5